


Zwężka niesymetryczna Geberit PE, krótka



Ilustracja przykładowa

PRZEZNACZENIE

- Do kanalizacji wewnątrz konstrukcji budowlanej
- Do kanalizacji zewnętrznej

CHARAKTERYSTYKA

- Niesymetryczny
- Odporny na promieniowanie UV

DANE TECHNICZNE

Materiał PE-HD

| Nr art. | DN | d, ø mm | d1, ø mm | A cm | H cm | h cm | h1 cm | K cm |
|--------------|---------|------------|-------------|---------|---------|---------|----------|---------|
| 361.558.16.1 | 50 / 40 | 50 | 40 | 0.5 | 8 | 3.5 | 3.7 | 2 |
| 363.558.16.1 | 56 / 40 | 56 | 40 | 0.8 | 8 | 3.5 | 3.7 | 2 |
| 363.561.16.1 | 56 / 50 | 56 | 50 | 0.3 | 8 | 3.5 | 3.7 | 2 |
| 364.558.16.1 | 60 / 40 | 63 | 40 | 1.2 | 8 | 3.5 | 3.7 | 2 |
| 364.561.16.1 | 60 / 50 | 63 | 50 | 0.7 | 8 | 3.5 | 3.7 | 2 |
| 364.566.16.1 | 60 / 56 | 63 | 56 | 0.4 | 8 | 3.5 | 3.7 | 2 |

| <i>Nr art.</i> | <i>DN</i> | <i>d, ø</i> <i>mm</i> | <i>d1, ø</i> <i>mm</i> | <i>A</i> <i>cm</i> | <i>H</i> <i>cm</i> | <i>h</i> <i>cm</i> | <i>h1</i> <i>cm</i> | <i>K</i> <i>cm</i> |
|---------------------|-----------|--------------------------|---------------------------|-----------------------|-----------------------|-----------------------|------------------------|-----------------------|
| 365.558.16.1 | 70 / 40 | 75 | 40 | 1.8 | 8 | 3.5 | 3.7 | 2 |
| 365.561.16.1 | 70 / 50 | 75 | 50 | 1.3 | 8 | 3.5 | 3.7 | 2 |
| 365.566.16.1 | 70 / 56 | 75 | 56 | 1 | 8 | 3.5 | 3.7 | 2 |
| 365.571.16.1 | 70 / 60 | 75 | 63 | 0.6 | 8 | 3.5 | 3.7 | 2 |
| 366.561.16.1 | 90 / 50 | 90 | 50 | 2 | 8 | 3.5 | 3.7 | 2 |
| 366.566.16.1 | 90 / 56 | 90 | 56 | 1.7 | 8 | 3.5 | 3.7 | 2 |
| 366.571.16.1 | 90 / 60 | 90 | 63 | 1.3 | 8 | 3.5 | 3.7 | 2 |
| 366.576.16.1 | 90 / 70 | 90 | 75 | 0.8 | 8 | 3.5 | 3.7 | 2 |
| 367.558.16.1 | 100 / 40 | 110 | 40 | 3.4 | 8 | 3.5 | 3.7 | 2 |
| 367.561.16.1 | 100 / 50 | 110 | 50 | 2.9 | 8 | 3.5 | 3.7 | 2 |
| 367.566.16.1 | 100 / 56 | 110 | 56 | 2.6 | 8 | 3.5 | 3.7 | 2 |
| 367.571.16.1 | 100 / 60 | 110 | 63 | 2.2 | 8 | 3.5 | 3.7 | 2 |
| 367.576.16.1 | 100 / 70 | 110 | 75 | 1.6 | 8 | 3.5 | 3.7 | 2 |

| <i>Nr art.</i> | <i>DN</i> | <i>d, ø</i> <i>mm</i> | <i>d1, ø</i> <i>mm</i> | <i>A</i> <i>cm</i> | <i>H</i> <i>cm</i> | <i>h</i> <i>cm</i> | <i>h1</i> <i>cm</i> | <i>K</i> <i>cm</i> |
|---------------------|-----------|--------------------------|---------------------------|-----------------------|-----------------------|-----------------------|------------------------|-----------------------|
| 367.581.16.1 | 100 / 90 | 110 | 90 | 0.9 | 8 | 3.5 | 3.7 | 2 |
| 368.561.16.1 | 125 / 50 | 125 | 50 | 3.6 | 8 | 3.5 | 3.7 | 2 |
| 368.566.16.1 | 125 / 56 | 125 | 56 | 3.3 | 8 | 3.5 | 3.7 | 2 |
| 368.571.16.1 | 125 / 60 | 125 | 63 | 2.9 | 8 | 3.5 | 3.7 | 2 |
| 368.576.16.1 | 125 / 70 | 125 | 75 | 2.3 | 8 | 3.5 | 3.7 | 2 |
| 368.581.16.1 | 125 / 90 | 125 | 90 | 1.6 | 8 | 3.5 | 3.7 | 2 |
| 368.586.16.1 | 125 / 100 | 125 | 110 | 0.7 | 8 | 3.5 | 3.7 | 2 |
| 369.586.16.1 | 150 / 100 | 160 | 110 | 2.3 | 8 | 3.5 | 3.7 | 2 |
| 369.588.16.1 | 150 / 125 | 160 | 125 | 1.6 | 8 | 3.5 | 3.7 | 2 |
| 369.591.16.1 | 150 / 140 | 160 | 140 | 1 | 8 | 3.5 | 3.7 | 2 |